



# TORQU3 PRESTIGE FULLY SYNTHETIC API 5W20 SN PLUS

(Premium Quality, Multigrade, High Performance Engine Oils)

TORQU3 multigrade gasoline engine oils are premium quality oils formulated using the latest technology. It works harder to protect the engine than conventional motor oils by preventing dirt and sludge build-up for better responsiveness and improved performance.

## PERFORMANCE BENEFITS

### PREMIUM FORMULATION

- Using the best SYNTHETIC base materials and additives to ensure efficiency and life of the engine. Specially formulated to protect high compression gasoline direct injection engines from the occurrence of Low Speed Pre-Ignition and Timing Chain wear. Ultimate high temperature oxidation control, provide against oil thickening at high temperatures.

### ENGINE CLEANLINESS

- High thermal stability provides a high standard of protection against piston deposits which, together with high performance dispersants, delivers excellent control of sludge and deposits in the engine.

### LOW ENGINE WEAR

- The combination of active anti-wear additives and good engine cleanliness controls engine wear giving long engine life, maintaining engine power and efficiency.

### THERMAL STABILITY

- Resists thermal breakdown even under non-routine high temperature excursions ensuring continued protection throughout the drain interval. Resists oil degradation throughout the recommended oil drain interval.

### MULTIGRADE VISCOSITY

- Easier cold starting compared with monograde oils.

### APPLICATIONS

- Suitable for Petrol engines of modern passenger vehicles with hybrid and conventional propulsion systems with and without turbocharging.

### MEETS SPECIFICATIONS & APPROVALS:

- API SN PLUS
- ILSAC GF-5
- MS-6395
- WSS-M2C945A1

### Protect the Environment

Dispose of used oils responsibly. Do not discharge into drains, soil or water.

TORQU3 API SN PLUS FULLY SYNTHETIC	
SAE Viscosity Grade	5W20
Kinematic viscosity at 40°C (cSt)	56.88
Kinematic viscosity at 100°C (cSt)	10.28
Density at 15°C	0.84
Flash point, °C	224
Pour point, °C	-47
Viscosity Index	167

These characteristics are typical of current production. Whilst future production will conform to TORQU3's specification, variations in these characteristics may occur.